




Central Strength Member
Loose Tube
Water-Blocking Yarn
Water-Blocking Tape
Strength Member
Rip cord
Outer Sheath

ADSS-12C SINGLE JACKET

Span 100m

PBT loose tube

Identification of product		ADSS-12B1.3-PE-100M CABLE	
Product application ● Aerial installation		Product information	
	Fiber	G652D	
	Fiber Color Code	Blue, Orange, Green, Brown, Grey, White	
	Loose tube color	Blue, Orange	
	Loose tube diameter	1.8mm	
	Center strength member	FRP	
	Center strength memberΦ	1.8mm	
	Water blocking mode	Water Blocking Yarn+ Water Blocking Tape	
	Strength member	Aramid Yarn	
	Ripcord	1 Polyester yarn	
Reference specification ● IEC-60794-1-21 ● YD/T 1460.4 ● YD/T 3350.1-2018	Sheath diameter	9.2±0.5 mm	
	Material	MDPE	
	Cable color	Black	
	Cable weight	63kg/km	
	Cable marking	As per customer requirements	
Packaging ● 4000m/drum ● Drumsizе: 1000*400*740mm		Properties of products	
	Tensile Strength	1000N/100mm	
	Min. Bending Radius	Short term: 25D Long term : 15D	
	Crush Performance	Short term: 1000N/100mm Long term : 300N/100mm	
	Suiting Line Voltage Class	Not more than 35kV	
	Meteorological condition	1.Wind : 20m/s 2.Ice : 0mm 3.Sag : 1.0~3.0% 4.Span : 100m	
	Temperature Range	-40℃~+70℃ when working or store	
		-10℃~+50℃ when laying	



+17863204446
+14073606163



8318 VIVARO ISLE WAY,
WINDERMERE FL.



SALES@ACLFIBER.COM